

GDS-99X Wireless Repeater

Explosion-Proof Signal Repeater for Wireless Gas Detection Systems

- * 255 Channel Repeater Function covers all addresses on network
- * Magnetic switches allow for easy field setup and monitoring
- * Input power range from +12V to +35VDC or external 110/220VAC
- * Separate antennas for receive and transmit optimize placement
- * Support for either 900 MHz (200 mW) or 2.4 GHz (125 mW) radio
- * Dual radios for simultaneous receive and transmit
- * Operating temperature range of -40°C to +60°C
- * Graphical LCD display with LED backlight
- * Operates on +12V for easy use with 12V solar power system
- * Manufactured in USA

The GDS-99X wireless repeater receives and re-broadcasts wireless signals from GDS Corp wireless gas monitors. The GDS-99X improves signal integrity and increases the range of wireless signals.

The GDS-99X supports 52 unique networks on 900 MHz radios and 76 unique networks on 2.4 GHz radios. Wireless 900 MHz radios broadcast 200 mW power while 2.4 GHz radios broadcast 125 mW power.

The GDS-99X operates over a range of +12VDC to +35VDC, enabling use with low cost 12V solar power systems (always use a low-voltage cutoff controller).

GX-99X Specifications:

Function: Signal repeater
 Power Input: +12-35VDC
 Current Draw: 150 mA MAX
 Display: 102x64 LCD
 Transflective sun-readable
 User Interface: Magnetic Wand
 Inputs: Wireless signals
 Outputs: Wireless signals
 Connectors: External N-Female (2)
 Dimensions: 5.4"L x 6.0"W x 12.2" H
 Certifications: C1, D1, C&D
 Ex db IIB Gb
 C1 Z1 AEx db ia IIB Gb
 Tamb -40C to +54C
 Warranty: One year limited



GDS-99X Order Guide

GDS-99X-FUNC-OPT1-OPT2 [X]	
FUNC	1 = Wireless Repeater
OPT1	1 = 900 MHz Radio 2 = 2.4 GHz Radio
OPT2	1 = +12 to +35VDC Power In 2 = 110/220 VAC Power In
[X]	[TAG] = Stainless steel tag



1245 Butler Road
 League City, Texas 77573
 409-927-2980 • 409-927-4180 (fax)
 www.gdscorp.com • info@gdscorp.com