

GASMAX DSX Gas Monitor

Dual Channel Explosion Proof Gas Monitor for Toxic Gases, Oxygen Depletion and Hydrocarbon Combustible Gases

- * Certified for use in Class I Div I hazardous locations
- * Monitor toxic gases, oxygen levels or hydrocarbon combustibles
- * Graphic display shows reading, alarm and fault conditions
- * Supports both local and remote sensors for easy installation
- * Non-intrusive user interface for calibration in hazardous areas
- * Power-up and post-calibration delays eliminate false alarms
- * Supports GDS-IR and GDS-IR2 infrared gas sensors
- * Dual channels support redundant sensors or monitor multiple hazards
- * Operates on +24VDC with +18 to +32VDC total range
- * Four alarm relays configurable for multi-sensor array logic
- * MODBUS wiring junction box allows for easy daisy chain setup
- * Setup in hazardous area requires only simple magnetic wand
- * Manufactured in USA

The **GASMAX DSX** gas monitor is an ideal solution for fixed ambient gas detection applications where multiple sensors are required. The monitor is designed to detect a wide range of toxic and combustible gases in potentially hazardous environments. The monitor operates on +18 to +32 volts DC and outputs an industry standard 4-20mA analog signal. Optional programmable alarm relays allow the GASMAX DSX to operate with a wide range of industry devices and system controllers.

Wide Variety of Available Sensors

The **GASMAX DSX** supports both local and remote electrochemical and infrared combustible sensors. Several electrochemical sensors, including hydrogen sulfide are available in low, medium and high ranges.

Non-Intrusive User Interface

The **GASMAX DSX** features non-intrusive magnetic switches that allow complete system configuration, regular calibration and product maintenance to be performed in the field without compromising the explosion-proof rating. The display screen always shows the current calibrated level of gas present at the sensor.

Flexible Output Options

In addition to an industry-standard 4-20mA current loop output, a built-in isolated RS-485 two-wire MODBUS® interface is available to communicate with controllers, PLCs or large



GASMAX DSX Transmitter



GDS-IR Infrared Sensor



Toxic Sensor

DCS system. When used with the any controller's MODBUS master port, multiple **GASMAX DSX** monitors can be daisy-chained up to 500m to minimize wiring. A special Modbus Wiring Junction Box option makes it possible to easily create the daisy chain wiring for power and Modbus signal.

Certifications

The **GASMAX DSX** is CSA and IECEx certified for use in hazardous areas and is ideal for power plants, refineries, tank farms, chemical plants, compressor stations, pipelines and other industrial installations where fixed gas detection is required for user safety and equipment protection. Please contact GDS Corp to discuss application details or to obtain a quote for monitors or complete gas detection systems.



1245 Butler Road
League City, Texas 77573
409-927-2980 • 409-927-4180 (fax)
www.gdscorp.com • info@gdscorp.com

GASMAX DSX SPECIFICATIONS	
Power Input	+18-32VDC, +24VDC nominal Operating current 315 mA@ 24VDC all options Transmitter only 50mA @ 24V, 65mA @ 18V
Display	High resolution graphical LCD transreflective (sunlight readable) screen with white LED backlight
User Interface	Three magnetic switches for non-intrusive setup and calibration in hazardous areas
Sensor Input	Supports local or remote toxic gas or infrared combustible / CO2 using four-wire digital interface
Alarm Settings	Two user-adjustable alarm settings
Standard Output	Dual industry-standard 4-20mA outputs; max 1000 ohm loop load
Optional Relay Out	Four alarm / fault relays configurable for alarm set points; latching and non-latching mode; multi-sensor array logic
Digital Out	Single isolated two-wire MODBUS serial slave port.
Optional Radio	No radio
Temp	Electronics -40°C to +40°C; Limits may vary depending on sensor Relative humidity 0-99% non-condensing
Housing	Aluminum instrument housing, 303 Stainless Steel sensor housing
Dimensions	5.25" W x 5.3" L x 4.95" H (Transmitter only); Approx 6 lbs 5.25" W x 15" L x 4.95" H (Transmitter + GDS-IR) Approx 11 lbs
Certifications	CSA: Class I Div 1 Groups B, C, D; T5 IECEX: Ex d IIC TS Gb UL 2075 (when used with UL-Approved GDS-IR)
Hardware Warranty	One-year limited warranty
Sensor Warranty	Varies with gas type (warranty subject to verification by GDS Corp)

GASMAX DSX Order Guide	
GM/DSX-SEN1[REM]-SEN2[REM]-OPT1 [X]	
SEN1	Select from list below For remote sensor, append [REM]
SEN2	Select from list below For remote sensor, append [REM]
OPT1	0 = No Relays 1 = 4x Alarm Relays
[X]	[SS] = Stainless steel enclosure [TAG] = Stainless steel tag [MJB] = Modbus wiring junction box

NOTES
Note 1: Certain toxic sensors for reactive gases require removal of explosion-proof flame arrestor
Note 2: Dual local sensors require Y-adaptor that will be reflected in price.

EC SENSORS		INFRARED SENSORS		INFRARED SENSORS	
10	Oxygen (O2), 0-25%	117	GDS-IR Methanol 0-100% LEL	136	GDS-IR Ethylidene Norbornene (ENB) 0-100% LEL
11	Carbon Monoxide (CO), 0-1000 ppm	118	GDS-IR Propylene 0-100% LEL	137	GDS-IR Carbon Dioxide 0-1.00% v/v
12	Chlorine (CL2), 0-20 ppm*	119	GDS-IR Ethylene 0-100% LEL	138	GDS-IR Carbon Dioxide 0-5000 ppm
13	Chlorine Dioxide (CLO2), 0-5.0 ppm	120	GDS-IR Hexane 0-100% LEL	139	GDS-IR Carbon Dioxide 0-2000 ppm
14	Hydrogen (H2), 0-4% by volume	121	GDS-IR Jet-A 0-100% LEL		
15	Hydrogen Sulfide (H2S), 0-100 ppm	122	GDS-IR Diesel 0-100% LEL	209	GDS-IR2 Acetylene, 0-100% LEL
29	Nitrogen Dioxide (NO2) 0-10 ppm	123	GDS-IR Gasoline 0-100% LEL	210	GDS-IR2 Methane, 0-100% LEL
		124	GDS-IR Isopropyl Alcohol 0-100% LEL	211	GDS-IR2 Propane 0-100% LEL
		125	GDS-IR Acetone 0-100% LEL	220	GDS-IR2 Methyl Acetate 0-100% LEL
		126	GDS-IR p-Xylene 0-100% LEL	221	GDS-IR2 Vinyl Acetate 0-100% LEL
		127	GDS-IR Ethylene Oxide 0-50% LEL	222	GDS-IR2 Acetic Acid 0-100% LEL
110	GDS-IR Methane 0-100% LEL 70°C	128	GDS-IR MEK 0-100% LEL	230	GDS-IR Methane 0-100% by volume
1HT	GDS-IR Methane 0-100% LEL 90°C	129	GDS-IR Styrene	231	GDS-IR2 Propane 0-100% by volume
111	GDS-IR Propane 0-100% LEL	130	GDS-IR Methane 0-100% by volume	232	GDS-IR2 Carbon Dioxide 0-5%
112	GDS-IR Isobutane 0-100% LEL	131	GDS-IR Propane 0-100% by volume	233	GDS-IR2 Carbon Dioxide 0-3.5%
113	GDS-IR Pentane 0-100% LEL	132	GDS-IR Carbon Dioxide 0-5% v/v	301	GDS-IR2 Ammonia 0-1000 ppm
114	GDS-IR Cyclopentane 0-100% LEL	133	GDS-IR Carbon Dioxide 0-3.5% v/v	302	GDS-IR2 Ammonia 0-2500 ppm
115	GDS-IR n-Butane 0-100% LEL	134	GDS-IR Propane 0-9.75% by volume (UEL)	303	GDS-IR2 Ammonia 0-1% v/v
116	GDS-IR Ethanol 0-100% LEL	135	GDS-IR Carbon Dioxide 0-2.00 v/v	304	GDS-IR2 Ammonia 0-10% v/v



1245 Butler Road
League City, Texas 77573
409-927-2980 • 409-927-4180 (fax)
www.gdscorp.com • info@gdscorp.com